# NSN 5315-01-173-3038

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-173-3038

# Head Diameter:

Between 0.360 inches and 0.450 inches

# Shank Diameter:

Between 0.2331 inches and 0.2346 inches

# **Detent Quantity:**

2

# **Actuation Method:**

Push button

## Grip Length:

Between 0.3937 inches and 0.4137 inches

## Actuation Type:

Push

# Shear Strength:

7118 double pounds per square inch

## Shoulder To Head End Distance:

0.935 inches

## Pin Center To Handle End Distance:

1.300 inches

# **Pin Attachment Type:**

Link or ring

# Detent To Tapered End Distance:

Between 0.360 inches and 0.410 inches

## Material:

Stainless steel handle

# **Material Specification:**

Qq-w-423 federal specification single material response handle or ams5673 assn standard single material response handle

### Surface Treatment:

Passivate handle

# Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

### **Style Designator:**

L handle

Shelf Life:

N/a

### Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A212a0

# Mil-std (military Standard):

Mil-s-6758 spec.