NSN 5315-01-175-3929

First End Style:

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-175-3929

| Square |
|--|
| Second End Style: |
| Chamfered |
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.250 inches |
| Shank Length: |
| 0.593 inches |
| Shoulder Width Across Flats: |
| 0.438 inches |
| Shank Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Overall Length: |
| 1.843 inches |
| Hole Arrangement Style: |
| One end drilled |
| First Hole Diameter: |
| Between 0.076 inches and 0.086 inches |
| Distance From Centerline Of Hole To End Of Pin: |
| 0.140 inches |
| Second End Taper Length: |
| Between 0.250 inches and 0.270 inches |
| Second End Relationship With First End: |
| Not identical |
| Thread Size: |
| 0.250 inches |
| Second Shank Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| First End Location: |
| Threaded end |
| Second End Tip Radius: |
| Between 0.060 inches and 0.090 inches |
| Second Shank Length: |
| 1.125 inches |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Mil-t-9047, type 3, cond a military specification single material response |
| |

NSN 5315-01-175-3929

Headless Shoulder Pin - Page 2 of 2



| Shoulder |
|---------------------------|
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |

Mil-std (military Standard):

Style Designator:

Mil-t-9047 spec.