

View Online at <https://aerobasegroup.com/nsn/5315-01-175-6666>

First End Style:

Chamfered

Second End Style:

Chamfered

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.660 inches and 0.680 inches

Shank Length:

Between 0.434 inches and 0.435 inches

Shoulder Diameter:

1.250 inches

Shank Diameter:

Between 1.500 inches and 1.520 inches

Overall Length:

Between 2.500 inches and 2.520 inches

Internal Drive Style:

Slot

First End Taper Length:

0.190 inches

Second End Taper Length:

0.050 inches

Second End Relationship With First End:

Not identical

Hardness Rating:

35.0 rockwell c and 38.0 rockwell c

Thread Size:

0.437 inches

Second Shank Diameter:

Between 0.619 inches and 0.620 inches

First End Location:

Unthreaded end

First End Taper Angle:

30.0 degrees

Second End Taper Angle:

45.0 degrees

Second Shank Length:

0.750 inches

Material:

Steel comp xm-12

Material Specification:

Ams 5659 assn standard single material response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0