

View Online at <https://aerobasegroup.com/nsn/5315-01-178-3989>

**Head Diameter:**

Between 0.360 inches and 0.450 inches

**Handle Length:**

Between 1.375 inches and 1.750 inches

**Shank Diameter:**

Between 0.187 inches and 0.188 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

W/s: radar, firefinder, an/tpq-36 and an/tpq-37

**Grip Length:**

Between 2.200 inches and 2.220 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

5150 double pounds per square inch

**Shoulder To Head End Distance:**

1.030 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

0.410 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Qq-s-763 federal specification single material response detent

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

T handle

**Specification Data:**

96906-ms17988 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0