NSN 5315-01-182-9574

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-182-9574

First End Style:

Chamfered

Second End Style:

Chamfered

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.259 inches

Shank Length:

0.226 inches

Shoulder Diameter:

0.438 inches

Shank Diameter:

Between 0.3125 inches and 0.3140 inches

Overall Length:

1.875 inches

Undercut Diameter:

Between 0.245 inches and 0.255 inches

Undercut Width:

0.080 inches

First End Taper Length:

0.800 inches

Second End Taper Length:

0.030 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.312 inches

Second Shank Diameter:

Between 0.3125 inches and 0.3140 inches

First End Location:

Tapered end

First End Taper Angle:

25.0 degrees

First End Tip Radius:

0.060 inches

Surface Finish:

125.0 microinches

Second End Taper Angle:

45.0 degrees

NSN 5315-01-182-9574

Headless Shoulder Pin - Page 2 of 2



Second Shank Length:

1.250 inches

Special Features:

Tapered end contains 2 wrench flats.

Material:

Stainless steel

Material Specification:

Ams 5629 ph13-8 -0, cond. A assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type i, ii, or iii federal specification single treatment response

Style Designator:

Undercut

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0