

View Online at <https://aerobasegroup.com/nsn/5315-01-183-5615>

First End Style:

Chamfered

Head Style:

Flat chamfer

Diameter:

Between 3.90 millimeters and 4.00 millimeters

Effective Length:

Between 38.00 millimeters and 39.00 millimeters

Undercut Diameter:

Between 2.95 millimeters and 3.00 millimeters

Under Head Length:

Between 41.50 millimeters and 42.50 millimeters

Undercut Width:

Between 0.74 millimeters and 0.82 millimeters

First End Taper Length:

Between 0.2 millimeters and 0.5 millimeters

Features Provided:

Casehardened

First End Taper Angle:

Between 43.0 degrees and 47.0 degrees

Pin Head Diameter:

Between 5.8 millimeters and 6.0 millimeters

Height:

Between 3.0 millimeters and 4.0 millimeters

Material:

Steel comp 8620

Material Specification:

Mil-s-8690, cond c military specification single material response

Surface Treatment:

Cadmium or nickel

Surface Treatment Specification:

Qq-c-320, cl 2e, type 2 federal specification 1st treatment response or mil-c-26074, cl 2, gr a military specification 2nd treatment response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-8690 spec.