# NSN 5315-01-184-5465

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-184-5465

### Handle Length:

Between 1.750 inches and 2.000 inches

#### Shank Diameter:

Between 0.2470 inches and 0.2495 inches

## **Detent Quantity:**

2

#### **Actuation Method:**

Push button

#### Grip Length:

Between 2.400 inches and 2.420 inches

#### Actuation Type:

Push

#### Hardness Rating:

40.0 rockwell c shank

#### Shoulder To Head End Distance:

1.550 inches

#### Pin Attachment Type:

Ring or hook

### **Detent To Tapered End Distance:**

0.380 inches

## Material:

Steel comp 630 shank or steel comp 632 shank

#### Material Specification:

Mil-s-6758 military specification 1st material response spindle or ams5643 assn standard 2nd material response spindle or ams5520 assn

standard 3rd material response spindle or ams5657 assn standard 3rd material response spindle

#### Surface Treatment:

Passivate shank

## Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses spindle

#### Style Designator:

T handle

#### **Specification Data:**

80205-nas1334 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

#### Fiig:

A212a0

### Mil-std (military Standard):

Mil-s-6758 spec.