

View Online at <https://aerobasegroup.com/nsn/5315-01-185-3770>

Handle Length:

Between 1.750 inches and 2.000 inches

Shank Diameter:

Between 0.2470 inches and 0.2495 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 2.000 inches and 2.020 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank

Shoulder To Head End Distance:

1.550 inches

Pin Attachment Type:

Ring or hook

Detent To Tapered End Distance:

0.380 inches

Material:

Steel comp 630 shank or steel comp 632 shank

Material Specification:

Mil-s-6758 military specification 1st material response spindle or ams5643 assn standard 2nd material response spindle or ams5520 assn standard 3rd material response spindle or ams5657 assn standard 3rd material response spindle

Surface Treatment:

Passivate shank

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses spindle

Style Designator:

T handle

Specification Data:

80205-nas1334 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.