# NSN 5315-01-191-3389

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-191-3389

## Head Diameter:

Between 0.297 inches and 0.327 inches

## Shank Diameter:

Between 0.1855 inches and 0.1885 inches

## **Ring Handle Diameter:**

1.000 inches

## **Detent Quantity:**

1

## **Actuation Method:**

Push button

Grip Length:

Between 0.200 inches and 0.220 inches

Actuation Type:

Push and pull

## Shoulder To Head End Distance:

# 0.562 inches

## Pin Attachment Type:

Ring

## **Detent To Tapered End Distance:**

0.329 inches

## Material:

Steel comp 302 shank or steel comp 304 shank or steel comp 304l shank or steel comp 305 shank or steel comp 309 shank or steel comp 310 shank or steel comp 316 shank or steel comp 316l shank or steel comp 317 shank or steel comp 321 shank or steel comp 347 shank

# Material Specification:

Qq-s-763 federal specification all material responses shank or mil-s-7720 military specification all material responses shank

## Surface Treatment:

Passivate shank

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank

## Style Designator:

Ring handle

## **Specification Data:**

81205-bac+18 manufacturers specification

## Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A212a0

# Mil-std (military Standard):

Mil-s-7720 spec.