NSN 5315-01-191-3399

Headless Shoulder Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-191-3399

First End Style: Square Shank Length: Between 0.185 inches and 0.195 inches Shoulder Diameter: Between 0.7017 inches and 0.7027 inches Shank Diameter: Between 0.5555 inches and 0.5570 inches Overall Length: Between 1.685 inches and 1.710 inches Second End Relationship With First End: Identical Hardness Rating: 43.0 rockwell c and 47.0 rockwell c Second Shank Diameter: Between 0.5555 inches and 0.5570 inches First End Location: Between 0.5555 inches and 0.5570 inches Second Shank Diameter: Between 0.5555 inches and 0.5570 inches First End Location: Both ends Surface Finish: 32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Both ends Surface Finish: 32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Material Specification: <t< th=""></t<>
Shank Length:Between 0.185 inches and 0.195 inchesShoulder Diameter:Between 0.7017 inches and 0.7027 inchesShank Diameter:Between 0.5555 inches and 0.5570 inchesOverall Length:Between 1.685 inches and 1.710 inchesSecond End Relationship With First End:IdenticalHardness Rating:43.0 rockwell c and 47.0 rockwell cSecond Shank Diameter:Between 0.5555 inches and 0.5570 inchesFirst End Location:Both endsSurface Finish:32.0 microinches shoulder outside diameterSecond Shank Length:Between 0.185 inches and 0.195 inchesFirst End Location:Between 0.185 inches and 0.195 inchesSteel comp xm-13Material:Steel comp xm-13Material Specification:
Between 0.185 inches and 0.195 inchesShoulder Diameter:Between 0.7017 inches and 0.7027 inchesShank Diameter:Between 0.5555 inches and 0.5570 inchesOverall Length:Between 1.685 inches and 1.710 inchesSecond End Relationship With First End:IdenticalHardness Rating:43.0 rockwell c and 47.0 rockwell cSecond Shank Diameter:Between 0.5555 inches and 0.5570 inchesFirst End Location:Both endsSurface Finish:32.0 microinches shoulder outside diameterSecond Shank Length:Between 0.185 inches and 0.195 inchesMaterial:Steel comp xm-13Material Specification:
Shoulder Diameter: Between 0.7017 inches and 0.7027 inches Shank Diameter: Between 0.5555 inches and 0.5570 inches Overall Length: Between 1.685 inches and 1.710 inches Second End Relationship With First End: Identical Hardness Rating: 43.0 rockwell c and 47.0 rockwell c Second Shank Diameter: Between 0.5555 inches and 0.5570 inches First End Location: Both ends Surface Finish: 32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13
Between 0.7017 inches and 0.7027 inches Shank Diameter: Between 0.5555 inches and 0.5570 inches Overall Length: Between 1.685 inches and 1.710 inches Second End Relationship With First End: Identical Hardness Rating: 43.0 rockwell c and 47.0 rockwell c Second Shank Diameter: Between 0.5555 inches and 0.5570 inches First End Location: Both ends Surface Finish: 32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Meterial Specification:
Shank Diameter:Between 0.5555 inches and 0.5570 inchesOverall Length:Between 1.685 inches and 1.710 inchesSecond End Relationship With First End:IdenticalHardness Rating:43.0 rockwell c and 47.0 rockwell cSecond Shank Diameter:Between 0.5555 inches and 0.5570 inchesFirst End Location:Both endsSurface Finish:32.0 microinches shoulder outside diameterSecond Shank Length:Between 0.185 inches and 0.195 inchesMaterial:Steel comp xm-13Material Specification:
Between 0.5555 inches and 0.5570 inches Overall Length: Between 1.685 inches and 1.710 inches Second End Relationship With First End: Identical Hardness Rating: 43.0 rockwell c and 47.0 rockwell c Second Shank Diameter: Between 0.5555 inches and 0.5570 inches First End Location: Both ends Surface Finish: 32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Material Specification:
Overall Length:Between 1.685 inches and 1.710 inchesSecond End Relationship With First End:IdenticalHardness Rating:43.0 rockwell c and 47.0 rockwell cSecond Shank Diameter:Between 0.5555 inches and 0.5570 inchesFirst End Location:Both endsSurface Finish:32.0 microinches shoulder outside diameterSecond Shank Length:Between 0.185 inches and 0.195 inchesMaterial:Steel comp xm-13Material Specification:
Between 1.685 inches and 1.710 inches Second End Relationship With First End: Identical Hardness Rating: 43.0 rockwell c and 47.0 rockwell c Second Shank Diameter: Between 0.5555 inches and 0.5570 inches First End Location: Both ends Surface Finish: 32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Material Specification:
Second End Relationship With First End: Identical Hardness Rating: 43.0 rockwell c and 47.0 rockwell c Second Shank Diameter: Between 0.5555 inches and 0.5570 inches First End Location: Both ends Surface Finish: 32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Material Specification:
Identical Hardness Rating: 43.0 rockwell c and 47.0 rockwell c Second Shank Diameter: Between 0.5555 inches and 0.5570 inches First End Location: Both ends Surface Finish: 32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Material Specification:
Hardness Rating:43.0 rockwell cand 47.0 rockwell cSecond Shank Diameter:Between 0.5555 inches and 0.5570 inchesFirst End Location:Both endsSurface Finish:32.0 microinches shoulder outside diameterSecond Shank Length:Between 0.185 inches and 0.195 inchesMaterial:Steel comp xm-13Material Specification:
43.0 rockwell c and 47.0 rockwell c Second Shank Diameter: Between 0.5555 inches and 0.5570 inches First End Location: Both ends Surface Finish: 32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Material Specification:
Second Shank Diameter: Between 0.5555 inches and 0.5570 inches First End Location: Both ends Surface Finish: 32.0 microinches shoulder outside diameter 32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Material Specification:
Between 0.5555 inches and 0.5570 inches First End Location: Both ends Surface Finish: 32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Material Specification:
First End Location:Both endsSurface Finish:32.0 microinches shoulder outside diameter32.0 microinches shoulder outside diameterSecond Shank Length:Between 0.185 inches and 0.195 inchesMaterial:Steel comp xm-13Material Specification:
Both endsSurface Finish:32.0 microinches shoulder outside diameterSecond Shank Length:Between 0.185 inches and 0.195 inchesMaterial:Steel comp xm-13Material Specification:
Surface Finish: 32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Material Specification:
32.0 microinches shoulder outside diameter Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Material Specification:
Second Shank Length: Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Material Specification:
Between 0.185 inches and 0.195 inches Material: Steel comp xm-13 Material Specification:
Material: Steel comp xm-13 Material Specification:
Steel comp xm-13 Material Specification:
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Chromium
Surface Treatment Specification:
Ps 13102, class a, fscm k0349 mfr ref single treatment response
Style Designator:
Shoulder
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0