

View Online at <https://aerobasegroup.com/nsn/5315-01-192-5290>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.340 inches

**Shank Length:**

0.400 inches

**Shoulder Width Across Flats:**

0.250 inches

**Shank Diameter:**

0.190 inches

**Overall Length:**

1.150 inches

**First End Taper Length:**

0.047 inches

**Second End Taper Length:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

260.0 brinell hultgren and 300.0 brinell hultgren

**Thread Size:**

0.190 inches

**Second Shank Diameter:**

0.227 inches

**First End Location:**

Chamfered end

**First End Taper Angle:**

45.0 degrees

**Second End Tip Radius:**

0.060 inches

**Second End Taper Angle:**

21.0 degrees

**Second Shank Length:**

0.440 inches

**Material:**

Steel comp 303se

**Material Specification:**

Astm a582 cres bar assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 type 3 federal specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0