## NSN 5315-01-194-8551

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-194-8551 **Head Diameter:** Between 0.890 inches and 0.960 inches Handle Length: Between 2.375 inches and 2.500 inches Shank Diameter: Between 0.7470 inches and 0.7485 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 2.100 inches and 2.120 inches **Actuation Type:** Push and pull **Hardness Rating:** 36.0 rockwell c spindle and 40.0 rockwell c spindle **Shear Strength:** 73600 double pound **Shoulder To Head End Distance:** 1.465 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** 0.790 inches Material: Steel comp 4130 spindle **Material Specification:** Mil-s-6758 military specification single material response spindle or mil-t-6736 military specification single material response spindle **Surface Treatment:** Cadmium spindle and chromate spindle **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response spindle **Style Designator:** T handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig:

No

A212a0

## NSN 5315-01-194-8551

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.