

View Online at <https://aerobasegroup.com/nsn/5315-01-197-3302>

Handle Length:

Between 2.070 inches and 2.170 inches

Shank Diameter:

Between 0.3720 inches and 0.3735 inches

Detent Quantity:

2

Lanyard Length:

6.000 inches

Actuation Method:

Push button

Grip Length:

Between 0.900 inches and 0.920 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank

Shear Strength:

18400 double pound

Shoulder To Head End Distance:

Between 1.360 inches and 1.410 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

Between 0.290 inches and 0.390 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-s-6758 military specification single material response spindle or mil-t-6736 military specification single material response spindle

Surface Treatment:

Cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response spindle

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.