NSN 5315-01-197-8212

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-197-8212 First End Style: Chamfered Second End Style: Counterbored w/o through hole **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.835 inches Width Between Flats: Between 0.375 inches and 0.379 inches First Step Diameter: Between 0.8273 inches and 0.8278 inches First Step Length: 1.246 inches **Second Step Diameter:** Between 0.5990 inches and 0.5994 inches **Second Step Length:** 1.090 inches **Third Step Diameter:** 0.500 inches Third Step Length: 0.900 inches **Internal Drive Style:** Socket **Second End Counterbore Depth:** 0.089 inches First End Taper Length: Between 0.060 inches and 0.070 inches Thready Qty Per Inch (tpi): Second End Relationship With First End: Not identical **Thread Size:** 0.500 inches **First End Location:** Threaded end First End Taper Angle: Between 44.5 degrees and 45.5 degrees

Surface Finish: 32.0 microinches

NSN 5315-01-197-8212 Headless Shoulder Pin - Page 2 of 2



Special Features:
Dry film lubricant
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A212a0