

View Online at <https://aerobasegroup.com/nsn/5315-01-199-0408>

Head Diameter:

0.310 inches

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Ring Handle Diameter:

1.060 inches

Detent Quantity:

2

Lanyard Length:

5.000 inches

Actuation Method:

Push button

Grip Length:

Between 0.900 inches and 0.920 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

Shoulder To Head End Distance:

0.780 inches

Pin Attachment Type:

Cable lanyard w/o terminations or hook or ring

Detent To Tapered End Distance:

Between 0.260 inches and 0.290 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response spindle and mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium spindle

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.