

View Online at <https://aerobasegroup.com/nsn/5315-01-199-4626>

**Head Style:**

Pan no. 2 (r1 not required in item description)

**Chamfer Length:**

Between 0.077 inches and 0.109 inches

**Diameter:**

Between 0.869 inches and 0.871 inches

**Under Head Length:**

Between 2.803 inches and 2.823 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.161 inches and 0.181 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.196 inches

**Hardness Rating:**

26.5 rockwell c and 32.0 rockwell c

**Pin Chamfer Angle:**

Between 14.5 degrees and 15.5 degrees

**Shear Strength:**

90200 double pound

**Pin Head Diameter:**

Between 1.046 inches and 1.078 inches

**Special Features:**

Shank end may have either a chamfer or radius at the option of the vendor

**Height:**

Between 0.109 inches and 0.141 inches

**Material:**

Steel comp 4037 or steel comp 4130 or steel comp 8630

**Material Specification:**

Ams 6300 military specification 1st material response or mil-s-6758 military specification 2nd material response or mil-s-8630 military specification 3rd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl 2 federal specification single treatment response

**Style Designator:**

Straight

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.