## NSN 5315-01-202-0698

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-202-0698 **Shank Diameter:** Between 0.3720 inches and 0.3735 inches **Detent Quantity:** 2 Lanyard Length: Between 4.500 inches and 5.500 inches **Actuation Method:** Push button **End Application:** Support equipment, b-1 aircraft **Grip Length:** Between 1.900 inches and 1.920 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c spindle Shear Strength: 20600 double pound **Shoulder To Head End Distance:** 1.450 inches Pin Center To Handle End Distance: Between 1.555 inches and 1.640 inches Pin Attachment Type: Cable lanyard w/terminations **Detent To Tapered End Distance:** Between 0.335 inches and 0.365 inches Material: Steel comp 630 spindle or steel comp 632 spindle **Material Specification:** Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle **Surface Treatment:** Passivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spindle **Style Designator:** L handle Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5315-01-202-0698

Quick Release Pin - Page 2 of 2



Fiig:

A212a0