

NSN 5315-01-203-8543 Headless Shoulder Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-01-203-8543 First End Style: Square **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.300 inches **Shank Length:** 0.330 inches **Shoulder Diameter:** Between 0.494 inches and 0.502 inches **Shank Diameter:** 0.375 inches **Overall Length:** 1.254 inches **Undercut Diameter:** 0.313 inches **Undercut Width:** 0.040 inches **Second Undercut Width:** Between 0.046 inches and 0.049 inches **Second Undercut Diameter:** Between 0.396 inches and 0.399 inches Second End Relationship With First End: Identical

Thread Size:

0.375 inches

Second Shank Diameter:

Between 0.494 inches and 0.502 inches

First End Location:

Both ends

Second Shank Length:

0.400 inches

Material:

Aluminum alloy 6061

Material Specification:

Astm b221-t6 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 type 2 cl 2 military specification single treatment response

NSN 5315-01-203-8543

Headless Shoulder Pin - Page 2 of 2



Style Designator:
Undercut
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0

Mil-std (military Standard):

Mil-a-8625 spec.