

View Online at <https://aerobasegroup.com/nsn/5315-01-204-1758>

First End Style:

Chamfered

Head Style:

Round w/wrench flats

Under Head Length:

2.262 inches

First Step Diameter:

Between 0.684 inches and 0.685 inches

First Step Length:

Between 1.037 inches and 1.047 inches

Second Step Diameter:

Between 0.498 inches and 0.499 inches

Second Step Length:

1.215 inches

Hole Arrangement Style:

Drilled through head

First Hole Diameter:

0.062 inches

Distance From Centerline Of Hole To End Of Pin:

1.000 inches

First End Taper Length:

0.045 inches

Width Across Flats:

Between 0.740 inches and 0.752 inches

First End Taper Angle:

45.0 degrees

Pin Head Diameter:

0.937 inches

Special Features:

Threaded end 0.500-20 unf-3a withlocking pin hole

Height:

0.250 inches

Material:

Steel comp 4340

Material Specification:

Mil-s-8844 cl 1 military specification single material response

Surface Treatment:

Cadmium shank

Surface Treatment Specification:

Qq-p-416, cl 2, type 2 federal specification single treatment response shank

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-8844 spec.