## NSN 5315-01-204-4271

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-204-4271 First End Style: Chamfered **Second End Style:** Square **Shank Length:** 1.950 inches **Shoulder Width Across Flats:** 1.870 inches **Overall Length:** 3.750 inches **Undercut Diameter:** 0.175 inches **Undercut Width:** 0.180 inches **Second Undercut Width:** 0.060 inches **Second Undercut Diameter:** 0.170 inches First End Taper Length: 0.050 inches **Second End Relationship With First End:** Not identical **Hardness Rating:** 89.0 rockwell superficial 15-n and 91.0 rockwell superficial 15-n **Second Shank Diameter:** 0.180 inches First End Location: Chamfered end First End Taper Angle: 30.0 degrees **Second Shank Length:** 0.940 inches **Special Features:** Second end square 0.25 inch by 0.25 inch Material: Steel comp 8620 **Material Specification:** Astm-a322 assn standard 1st material response or astm-a331 assn standard 2nd material response **Surface Treatment:** Phosphate

**Surface Treatment Specification:** 

Mil-p-16232 type m or z, cl 2 military standard single treatment response

## NSN 5315-01-204-4271

Headless Shoulder Pin - Page 2 of 2



Style Designator:
Undercut
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
Demilitarization:

Mil-std (military Standard):

Mil-p-16232 spec.