NSN 5315-01-205-1119

Threaded Straight Pin - Page 1 of 2

First End Style:



View Online at https://aerobasegroup.com/nsn/5315-01-205-1119

| Square |
|--|
| Second End Style: |
| Chamfered |
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.380 inches |
| Pinlength: |
| 6.090 inches |
| Pindiameter: |
| 0.6250 inches |
| Second End Taper Length: |
| 0.940 inches |
| Second End Relationship With First End: |
| Not identical |
| Hardness Rating: |
| 30.0 rockwell c and 38.0 rockwell c |
| Thread Size: |
| 0.625 inches |
| First End Location: |
| Square end |
| Pin Grip Length: |
| 4.770 inches |
| Second End Tip Radius: |
| 0.940 inches |
| Second End Taper Angle: |
| 30.0 degrees |
| Special Features: |
| Item has groove 0.502 in. Lg x 0.500 in. Wide, 2.750 in.From first end |
| Material: |
| Steel comp 1030 or steel comp 1050 |
| Material Specification: |
| Astm a576 assn standard single material response |
| Surface Treatment: |
| Phosphate manganese |
| Surface Treatment Specification: |
| D0d-p-16232 military specification single treatment response |
| Thread Series Designator: |
| Unf |

NSN 5315-01-205-1119

Threaded Straight Pin - Page 2 of 2



| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |

Mil-std (military Standard):

spec.