

View Online at <https://aerobasegroup.com/nsn/5315-01-205-5211>

Shank Diameter:

Between 24.92 millimeters and 24.96 millimeters

Detent Quantity:

2

Lanyard Length:

Between 3.500 inches and 4.500 inches

Actuation Method:

Push button

Grip Length:

Between 25.0 millimeters and 25.6 millimeters

Actuation Type:

Push

Hardness Rating:

58.0 rockwell c detent and 62.0 rockwell c detent

Shear Strength:

560661 double newtons per square millimeter

Shoulder To Head End Distance:

Between 54.42 millimeters and 54.48 millimeters

Pin Center To Handle End Distance:

Between 92.68 millimeters and 92.74 millimeters

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

22.0 millimeters

Material:

Steel uns k08500 spring

Material Specification:

Qq-w-470 federal specification single material response spring

Surface Treatment:

Passivate detent

Surface Treatment Specification:

Qq-p-416, type ii, class 2 military specification 1st treatment response button or mil-a-8625 military specification 2nd treatment response button

Style Designator:

L handle

Specification Data:

84256-52917s8gl25w/lt1504-c8-4 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

spec.