

View Online at <https://aerobasegroup.com/nsn/5315-01-205-5211>

**Shank Diameter:**

Between 24.92 millimeters and 24.96 millimeters

**Detent Quantity:**

2

**Lanyard Length:**

Between 3.500 inches and 4.500 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 25.0 millimeters and 25.6 millimeters

**Actuation Type:**

Push

**Hardness Rating:**

58.0 rockwell c detent and 62.0 rockwell c detent

**Shear Strength:**

560661 double newtons per square millimeter

**Shoulder To Head End Distance:**

Between 54.42 millimeters and 54.48 millimeters

**Pin Center To Handle End Distance:**

Between 92.68 millimeters and 92.74 millimeters

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

22.0 millimeters

**Material:**

Steel uns k08500 spring

**Material Specification:**

Qq-w-470 federal specification single material response spring

**Surface Treatment:**

Passivate detent

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 military specification 1st treatment response button or mil-a-8625 military specification 2nd treatment response button

**Style Designator:**

L handle

**Specification Data:**

84256-52917s8gl25w/lt1504-c8-4 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

spec.