## NSN 5315-01-209-5687

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-209-5687 **Head Diameter:** 0.449 inches **Shank Diameter:** Between 0.3886 inches and 0.3917 inches **Ring Handle Diameter:** 1.187 inches **Detent Quantity:** 2 Lanyard Length: Between 143.65 millimeters and 156.35 millimeters **Actuation Method:** Handle **Grip Length:** Between 45.000 millimeters and 45.508 millimeters **Actuation Type:** Pull and push **Hardness Rating:** 58.0 rockwell c and 62.0 rockwell c detent **Shear Strength:** 22770 double pounds per square inch **Shoulder To Head End Distance:** 0.562 inches Pin Attachment Type: Cable lanyard w/terminations **Detent To Tapered End Distance:** 0.390 inches Material: Steel head **Material Specification:** Qq-w-470 federal specification single material response spring **Surface Treatment:** Passivate detent **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response spring **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5315-01-209-5687

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.