

View Online at <https://aerobasegroup.com/nsn/5315-01-210-8481>

**First End Style:**

Chamfered

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

Between 0.078 inches and 0.082 inches

**Second Hole Diameter:**

Between 0.078 inches and 0.082 inches

**Distance From Centerline Of Hole To End Of Pin:**

Between 0.360 inches and 0.370 inches

**Center To Center Distance Between Holes:**

Between 2.160 inches and 2.170 inches

**Pinlength:**

Between 2.903 inches and 2.913 inches

**Pindiameter:**

Between 0.3100 inches and 0.3110 inches

**First End Taper Length:**

Between 0.020 inches and 0.040 inches

**Second End Relationship With First End:**

Identical

**First End Taper Angle:**

Between 40.0 degrees and 50.0 degrees

**Special Features:**

Thru hole 0.125 to 0.130 in. 1.454 in. Nom from each end 90 degrees of other two holes

**Material:**

Stainless steel

**Material Specification:**

Ams 5643 assn standard 1st material response or mil-h-6875 military specification 2nd material response

**Surface Treatment:**

Oxide film and passivate

**Surface Treatment Specification:**

Mil-I-8937 military specification 1st treatment response

**Supplementary Features:**

30 in. Hook spring supp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-h-6875 spec.