

View Online at <https://aerobasegroup.com/nsn/5315-01-213-5562>

First End Style:

Chamfered

Second End Style:

Slotted

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.415 inches

Shank Length:

1.720 inches

Shoulder Diameter:

0.138 inches

Shank Diameter:

Between 0.0932 inches and 0.0934 inches

Overall Length:

Between 2.130 inches and 2.140 inches

Second End Slot Width:

Between 0.025 inches and 0.032 inches

First End Taper Length:

0.050 inches

Second End Slot Depth:

Between 0.040 inches and 0.050 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.138 inches

Shear Strength:

200000 double pounds per square inch

First End Location:

Shank end

First End Taper Angle:

15.0 degrees

Surface Finish:

16.0 microinches outside diameter

Material:

Steel comp 431

Material Specification:

Mil-s-18732 military specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-18732 spec.