## NSN 5315-01-213-5563

First End Style:

Second End Style:

**Thread Direction:** 

Thread Length:

Square

За

Chamfered
Thread Class:

Right-hand

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-213-5563

0.345 inches
Shank Length:
0.533 inches
Shoulder Diameter:
0.375 inches
Shank Diameter:
Between 0.1890 inches and 0.1895 inches
Overall Length:
1.223 inches
Hole Arrangement Style:
One end drilled
First Hole Diameter:
Between 0.076 inches and 0.086 inches
Distance From Centerline Of Hole To End Of Pin:
0.140 inches
Second End Taper Length:
Between 0.170 inches and 0.210 inches
Second End Relationship With First End:
Not identical
Thread Size:
Thread Size: 0.190 inches
0.190 inches
0.190 inches Second Shank Diameter:
0.190 inches  Second Shank Diameter:  Between 0.1851 inches and 0.1863 inches
0.190 inches  Second Shank Diameter:  Between 0.1851 inches and 0.1863 inches  First End Location:
0.190 inches  Second Shank Diameter:  Between 0.1851 inches and 0.1863 inches  First End Location:  Threaded end
0.190 inches  Second Shank Diameter:  Between 0.1851 inches and 0.1863 inches  First End Location:  Threaded end  Second End Tip Radius:
0.190 inches  Second Shank Diameter:  Between 0.1851 inches and 0.1863 inches  First End Location:  Threaded end  Second End Tip Radius:  Between 0.060 inches and 0.090 inches
0.190 inches  Second Shank Diameter:  Between 0.1851 inches and 0.1863 inches  First End Location:  Threaded end  Second End Tip Radius:  Between 0.060 inches and 0.090 inches  Second End Taper Angle:
0.190 inches  Second Shank Diameter:  Between 0.1851 inches and 0.1863 inches  First End Location:  Threaded end  Second End Tip Radius:  Between 0.060 inches and 0.090 inches  Second End Taper Angle:  45.0 degrees
0.190 inches  Second Shank Diameter:  Between 0.1851 inches and 0.1863 inches  First End Location:  Threaded end  Second End Tip Radius:  Between 0.060 inches and 0.090 inches  Second End Taper Angle:  45.0 degrees  Second Shank Length:
0.190 inches  Second Shank Diameter:  Between 0.1851 inches and 0.1863 inches  First End Location: Threaded end  Second End Tip Radius:  Between 0.060 inches and 0.090 inches  Second End Taper Angle:  45.0 degrees  Second Shank Length:  0.565 inches

## NSN 5315-01-213-5563

Headless Shoulder Pin - Page 2 of 2



Material	Spec	cific	ation

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or astm a582 assn standard 3rd material response

Surtace	Treatment	•

**Passivate** 

## **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:** 

Shoulder

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A212a0