# NSN 5315-01-213-5563

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-213-5563

First End Style:

Square

Second End Style:

Chamfered

Thread Class:

За

## **Thread Direction:**

**Right-hand** 

Thread Length:

0.345 inches

Shank Length:

0.533 inches

Shoulder Diameter:

0.375 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Overall Length:

1.223 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.076 inches and 0.086 inches

## Distance From Centerline Of Hole To End Of Pin:

0.140 inches

## Second End Taper Length:

Between 0.170 inches and 0.210 inches

## Second End Relationship With First End:

Not identical

## Thread Size:

0.190 inches

## Second Shank Diameter:

Between 0.1851 inches and 0.1863 inches

#### First End Location:

Threaded end

## Second End Tip Radius:

Between 0.060 inches and 0.090 inches

## Second End Taper Angle:

45.0 degrees

## Second Shank Length:

0.565 inches

Material:

Steel comp 302 or steel comp 304 or steel comp 303se

## NSN 5315-01-213-5563

Headless Shoulder Pin - Page 2 of 2



## **Material Specification:**

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or astm a582 assn standard 3rd material response

Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Shoulder

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A212a0