## NSN 5315-01-214-1515

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-214-1515 **Shank Diameter:** Between 0.2470 inches and 0.2495 inches **Button Handle Diameter:** 1.203 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 4.000 inches and 4.020 inches **Actuation Type:** Pull and push Hardness Rating: 54.0 rockwell c and 64.0 rockwell c detent **Shear Strength:** 9200 double pounds per square inch **Shoulder To Head End Distance:** 1.290 inches Pin Attachment Type: Link **Detent To Tapered End Distance:** 0.406 inches Material: Stainless steel shank **Material Specification:** Qq-s-763, cl 440c federal specification single material response detent **Surface Treatment:** Passivate head **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification 1st treatment response spindle **Style Designator: Button Specification Data:** 80205-nas1354 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A212a0

## NSN 5315-01-214-1515

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.