## NSN 5315-01-216-7958

Headless Grooved Pin - Page 1 of 2

First End Style:



View Online at https://aerobasegroup.com/nsn/5315-01-216-7958

| Chamfered  |
|--|
| Second End Style:  |
| Chamfered and counterbored   |
| Overall Length:  |
| 10.100 inches  |
| Diameter:  |
| Between 0.992 inches and 0.995 inches                                    |
| Hole Arrangement Style:  |
| Both end drilled   |
| First Hole Diameter:   |
| 0.190 inches   |
| Second Hole Diameter:  |
| 0.190 inches   |
| Distance From Centerline Of Hole To End Of Pin:                          |
| Between 1.926 inches and 1.929 inches                                    |
| Center To Center Distance Between Holes:                                 |
| Between 8.176 inches and 8.179 inches                                    |
| Second End Counterbore Diameter:   |
| 0.343 inches   |
| First End Taper Length:  |
| 0.120 inches   |
| Second End Taper Length:   |
| 0.120 inches   |
| Second End Relationship With First End:                                  |
| Not identical  |
| Hardness Rating:   |
| 32.0 rockwell c and 38.0 rockwell c                                      |
| First End Location:  |
| Unthreaded end   |
| First End Taper Angle:   |
| 30.0 degrees   |
| Surface Finish:  |
| 63.0 microinches outside diameter  |
| Second End Taper Angle:  |
| 30.0 degrees   |
| Special Features:  |
| Holes grooves style  |
| Material:  |
| Steel comp 4140 or steel comp 4340 or steel comp 8640 or steel comp 8740 |
| Surface Treatment:   |
| Cadmium and chromate or zinc and chromate                                |
|  |

## NSN 5315-01-216-7958

Headless Grooved Pin - Page 2 of 2



## **Surface Treatment Specification:**

Qq-p-416 ty2 cl3 federal specification 1st treatment response or qq-z-325 ty2 cl3 federal specification 2nd treatment response

**Style Designator:** 

Circular groove

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A212a0