

View Online at <https://aerobasegroup.com/nsn/5315-01-218-9968>

First End Style:

Chamfered and counterbored

Thread Direction:

Right-hand

Thread Length:

27.0 millimeters

Shank Length:

25.0 millimeters

Shoulder Diameter:

45.0 millimeters

Shank Diameter:

Between 29.5 millimeters and 30.0 millimeters

Overall Length:

Between 248.0 millimeters and 252.0 millimeters

End Application:

Hemtt family (heavy expanded mobility tactical trucks); 2320-01-097-0260 hiab crane (hemtt)

Second End Counterbore Diameter:

22.0 millimeters

First End Counterbore Depth:

27.0 millimeters

Second End Counterbore Depth:

15.0 millimeters

First End Taper Length:

1.0 millimeters

Second End Taper Length:

2.0 millimeters

Second End Relationship With First End:

Not identical

Thread Size:

10.0 millimeters

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Second End Taper Angle:

45.0 degrees

Thread Tolerance Class:

6h internal

Special Features:

1 slot 7 mm from edge 1 countersunk through hole 48 mm from end

Style Designator:

Shoulder

Thread Series Designator:

M

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0