NSN 5315-01-218-9968

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-218-9968

First End Style:
Chamfered and counterbored
Thread Direction:
Right-hand
Thread Length:
27.0 millimeters
Shank Length:
25.0 millimeters
Shoulder Diameter:
45.0 millimeters
Shank Diameter:
Between 29.5 millimeters and 30.0 millimeters
Overall Length:
Between 248.0 millimeters and 252.0 millimeters
End Application:
Hemtt family (heavy expanded mobility tactical trucks); 2320-01-097-0260 hiab crane (hemtt)
Second End Counterbore Diameter:
22.0 millimeters
First End Counterbore Depth:
27.0 millimeters
Second End Counterbore Depth:
Second End Counterbore Depth: 15.0 millimeters
•
15.0 millimeters
15.0 millimeters First End Taper Length:
15.0 millimeters First End Taper Length: 1.0 millimeters
15.0 millimeters First End Taper Length: 1.0 millimeters Second End Taper Length:
15.0 millimeters First End Taper Length: 1.0 millimeters Second End Taper Length: 2.0 millimeters
15.0 millimeters First End Taper Length: 1.0 millimeters Second End Taper Length: 2.0 millimeters Second End Relationship With First End:
15.0 millimeters First End Taper Length: 1.0 millimeters Second End Taper Length: 2.0 millimeters Second End Relationship With First End: Not identical
15.0 millimeters First End Taper Length: 1.0 millimeters Second End Taper Length: 2.0 millimeters Second End Relationship With First End: Not identical Thread Size:
15.0 millimeters First End Taper Length: 1.0 millimeters Second End Taper Length: 2.0 millimeters Second End Relationship With First End: Not identical Thread Size: 10.0 millimeters
15.0 millimeters First End Taper Length: 1.0 millimeters Second End Taper Length: 2.0 millimeters Second End Relationship With First End: Not identical Thread Size: 10.0 millimeters First End Location:
First End Taper Length: 1.0 millimeters Second End Taper Length: 2.0 millimeters Second End Relationship With First End: Not identical Thread Size: 10.0 millimeters First End Location: Threaded end
First End Taper Length: 1.0 millimeters Second End Taper Length: 2.0 millimeters Second End Relationship With First End: Not identical Thread Size: 10.0 millimeters First End Location: Threaded end First End Taper Angle:
15.0 millimeters First End Taper Length: 1.0 millimeters Second End Taper Length: 2.0 millimeters Second End Relationship With First End: Not identical Thread Size: 10.0 millimeters First End Location: Threaded end First End Taper Angle: 45.0 degrees
First End Taper Length: 1.0 millimeters Second End Taper Length: 2.0 millimeters Second End Relationship With First End: Not identical Thread Size: 10.0 millimeters First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Taper Angle:
First End Taper Length: 1.0 millimeters Second End Taper Length: 2.0 millimeters Second End Relationship With First End: Not identical Thread Size: 10.0 millimeters First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Taper Angle: 45.0 degrees
First End Taper Length: 1.0 millimeters Second End Taper Length: 2.0 millimeters Second End Relationship With First End: Not identical Thread Size: 10.0 millimeters First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Taper Angle: 45.0 degrees Thread Tolerance Class:

Shoulder

Style Designator:

NSN 5315-01-218-9968

Headless Shoulder Pin - Page 2 of 2



Th	rea	d 9	Series	Desig	nator:
111	ıı ca	u,	סטו וטס	DESIG	nator.

Μ

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0