NSN 5315-01-219-4966

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-219-4966 **Head Diameter:** Between 0.595 inches and 0.655 inches **Shank Diameter:** Between 0.3905 inches and 0.3920 inches **Detent Quantity:** 2 Lanyard Length: Between 4.500 inches and 4.550 inches **Actuation Method:** Push button **Grip Length:** Between 60.0 millimeters and 60.6 millimeters **Actuation Type:** Push **Hardness Rating:** 58.0 rockwell c and 62.0 rockwell c detent **Shear Strength:** 22496 double pounds per square inch **Shoulder To Head End Distance:** 1.550 inches Pin Center To Handle End Distance: Between 1.918 inches and 1.948 inches Pin Attachment Type: Cable lanyard w/terminations **Detent To Tapered End Distance:** Between 0.315 inches and 0.393 inches Material: Steel comp 630 spindle **Material Specification:** Qq-s-763 federal specification single material response detent **Surface Treatment:** Passivate spring **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spring **Style Designator:** L handle Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5315-01-219-4966

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-a-8625 spec.