

View Online at <https://aerobasegroup.com/nsn/5315-01-219-4966>

Head Diameter:

Between 0.595 inches and 0.655 inches

Shank Diameter:

Between 0.3905 inches and 0.3920 inches

Detent Quantity:

2

Lanyard Length:

Between 4.500 inches and 4.550 inches

Actuation Method:

Push button

Grip Length:

Between 60.0 millimeters and 60.6 millimeters

Actuation Type:

Push

Hardness Rating:

58.0 rockwell c and 62.0 rockwell c detent

Shear Strength:

22496 double pounds per square inch

Shoulder To Head End Distance:

1.550 inches

Pin Center To Handle End Distance:

Between 1.918 inches and 1.948 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

Between 0.315 inches and 0.393 inches

Material:

Steel comp 630 spindle

Material Specification:

Qq-s-763 federal specification single material response detent

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-a-8625 spec.