## NSN 5315-01-224-3790



Headless Shoulder Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-01-224-3790 First End Style: Chamfered **Shank Length:** 0.280 inches Shoulder Diameter: Between 0.5005 inches and 0.5008 inches **Shank Diameter:** 0.460 inches **Overall Length:** 3.250 inches **Undercut Diameter:** 0.380 inches **Undercut Width:** 0.160 inches **Second Undercut Width:** 0.160 inches **Second Undercut Diameter:** 0.380 inches First End Taper Length: 0.180 inches Second End Relationship With First End: Identical **Second Shank Diameter:** 0.460 inches **First End Location:** Both ends First End Taper Angle: 33.7 degrees

Second Shank Length:

0.280 inches

Material:

Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1025 or steel comp 1012 or steel comp 1023

**Surface Treatment:** 

Cadmium and chromate or zinc and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl1 federal specification 1st treatment response or astm b633, type 2 assn standard 2nd treatment response

**Style Designator:** 

Undercut

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5315-01-224-3790

Headless Shoulder Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0