

View Online at <https://aerobasegroup.com/nsn/5315-01-226-8515>

**First End Style:**

Chamfered and countersunk

**Second End Style:**

Chamfered and counterbored

**Hole Arrangement Style:**

Drilled through center

**First Hole Diameter:**

0.500 inches

**Pinlength:**

Between 7.500 inches and 7.530 inches

**Pindiameter:**

Between 1.4980 inches and 1.4990 inches

**Second End Counterbore Diameter:**

Between 1.000 inches and 1.030 inches

**Second End Counterbore Depth:**

1.120 inches

**First End Taper Length:**

0.060 inches

**Second End Taper Length:**

0.060 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

46.0 rockwell c and 48.0 rockwell c

**First End Taper Angle:**

30.0 degrees

**Criticality Code Justification:**

Achu

**First End Countersink Angle:**

60.0 degrees

**First End Countersink Diameter:**

0.880 inches

**Second End Taper Angle:**

30.0 degrees

**Material:**

Steel comp 4330

**Material Specification:**

G-1010, fscm 13002 mfr ref single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0