## NSN 5315-01-227-0678

Headless Shoulder Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-227-0678

First End Style:ChamferedSecond End Style:Threaded and counterboredShoulder Diameter:Between 1.052 inches and 1.056 inchesShank Diameter:Between 1.052 inches and 1.056 inchesOverall Length:14.264 inchesUndercut Diameter:	
Second End Style: Threaded and counterbored Shoulder Diameter: Between 1.052 inches and 1.056 inches Shank Diameter: Between 1.052 inches and 1.056 inches Overall Length: 14.264 inches	
Threaded and counterbored Shoulder Diameter: Between 1.052 inches and 1.056 inches Shank Diameter: Between 1.052 inches and 1.056 inches Overall Length: 14.264 inches	
Shoulder Diameter: Between 1.052 inches and 1.056 inches Shank Diameter: Between 1.052 inches and 1.056 inches Overall Length: 14.264 inches	
Between 1.052 inches and 1.056 inches Shank Diameter: Between 1.052 inches and 1.056 inches Overall Length: 14.264 inches	
Shank Diameter:         Between 1.052 inches and 1.056 inches         Overall Length:         14.264 inches	
Between 1.052 inches and 1.056 inches Overall Length: 14.264 inches	
Overall Length: 14.264 inches	
14.264 inches	
Undercut Diameter:	
Between 0.817 inches and 0.819 inches	
Second Undercut Width:	
0.188 inches	
Second Undercut Diameter:	
Between 0.817 inches and 0.819 inches	
First Hole Diameter:	
Between 0.250 inches and 0.256 inches	
First End Taper Length:	
0.060 inches	
Second End Relationship With First End:	
Not identical	
Second Shank Diameter:	
Between 1.1200 inches and 1.1209 inches	
First End Taper Angle:	
45.0 degrees	
Second Shank Length:	
12.356 inches	
Material:	
Steel comp xm-13	
Material Specification:	
Ams 5629 assn standard single material response	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A212a0	