NSN 5315-01-227-0678

Headless Shoulder Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-227-0678

First End Style:
Chamfered
Second End Style:
Threaded and counterbored
Shoulder Diameter:
Between 1.052 inches and 1.056 inches
Shank Diameter:
Between 1.052 inches and 1.056 inches
Overall Length:
14.264 inches
Undercut Diameter:
Between 0.817 inches and 0.819 inches
Second Undercut Width:
0.188 inches
Second Undercut Diameter:
Between 0.817 inches and 0.819 inches
First Hole Diameter:
Between 0.250 inches and 0.256 inches
First End Taper Length:
0.060 inches
Second End Relationship With First End:
Not identical
•
Not identical
Not identical Second Shank Diameter:
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle:
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle: 45.0 degrees
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle: 45.0 degrees Second Shank Length:
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle: 45.0 degrees Second Shank Length: 12.356 inches
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle: 45.0 degrees Second Shank Length: 12.356 inches Material:
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle: 45.0 degrees Second Shank Length: 12.356 inches Material: Steel comp xm-13
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle: 45.0 degrees Second Shank Length: 12.356 inches Material: Steel comp xm-13 Material Specification:
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle: 45.0 degrees Second Shank Length: 12.356 inches Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle: 45.0 degrees Second Shank Length: 12.356 inches Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Shelf Life:
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle: 45.0 degrees Second Shank Length: 12.356 inches Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Shelf Life: N/a
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle: 45.0 degrees Second Shank Length: 12.356 inches Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Shelf Life: N/a
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle: 45.0 degrees Second Shank Length: 12.356 inches Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Shelf Life: N/a Unit Of Measure:
Not identical Second Shank Diameter: Between 1.1200 inches and 1.1209 inches First End Taper Angle: 45.0 degrees Second Shank Length: 12.356 inches Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Shelf Life: N/a Unit Of Measure: Demilitarization: