

View Online at <https://aerobasegroup.com/nsn/5315-01-228-4885>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered w/thru hole

**Pinlength:**

Between 2.490 inches and 2.510 inches

**Pindiameter:**

Between 0.7501 inches and 0.7503 inches

**First End Taper Length:**

Between 0.094 inches and 0.250 inches

**Second End Taper Length:**

Between 0.094 inches and 0.250 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

36.0 rockwell c and 42.0 rockwell c

**First End Taper Angle:**

25.0 degrees

**Surface Finish:**

16.0 microinches

**Second End Taper Angle:**

Between 20.0 degrees and 30.0 degrees

**Special Features:**

End of pin has a drilled hole 0.410-0.510 in deep, threaded hole .250-unf-2b, made from ms16555, surface finish for hole 125 microinches

**Material:**

Steel comp 410 or steel comp 416

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0