## NSN 5315-01-229-8340

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-229-8340 **Head Diameter:** 0.750 inches **Shank Diameter:** Between 0.3095 inches and 0.3120 inches **Ring Handle Diameter:** 1.063 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 0.800 inches and 0.820 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c spindle **Shear Strength:** 14400 double pound **Shoulder To Head End Distance:** 1.490 inches Pin Attachment Type: Ring or hook **Detent To Tapered End Distance:** 0.400 inches Material: Steel comp 632 or steel comp 630 spindle **Material Specification:** Ams 5520 assn standard 1st material response or ams 5657 assn standard 1st material response or ams 5643 assn standard 2nd material response spindle **Surface Treatment:** Passivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spindle **Style Designator:** Ring handle **Specification Data:** 80205-nas1335 professional/industrial association standard Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5315-01-229-8340

Quick Release Pin - Page 2 of 2



Fiig:

A212a0