

View Online at <https://aerobasegroup.com/nsn/5315-01-230-0093>

Shank Diameter:

Between 0.3720 inches and 0.3735 inches

Button Handle Diameter:

0.875 inches

Detent Quantity:

2

Lanyard Length:

Between 4.750 inches and 5.250 inches

Actuation Method:

Push button

Grip Length:

Between 1.900 inches and 1.920 inches

Actuation Type:

Push

Shear Strength:

18400 double pound

Shoulder To Head End Distance:

1.040 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

Between 0.335 inches and 0.365 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response shank or mil-s-6758 military specification single material response shank

Surface Treatment:

Cadmium spindle or cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification 1st treatment response spindle or qq-p-416, type 2, cl 2 federal specification 2nd treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.