NSN 5315-01-230-3705

Headless Shoulder Pin - Page 1 of 2

First End Style:

Style Designator:

Shoulder



View Online at https://aerobasegroup.com/nsn/5315-01-230-3705

Chamfered
Second End Style:
Chamfered
Thread Class:
2b
Thread Direction:
Right-hand
Thread Length:
0.500 inches
First Step Diameter:
0.620 inches
First Step Length:
0.500 inches
Second Step Diameter:
Between 0.445 inches and 0.448 inches
Second Step Length:
1.250 inches
Third Step Diameter:
Between 0.345 inches and 0.350 inches
Third Step Length:
0.940 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.190 inches
First End Location:
Threaded end
Second End Taper Angle:
30.0 degrees
Special Features:
Pin straight headless 2.190 in. Long and 0.190 in. Diameter welded through second shoulder 2.190 from second end
Material:
Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020
or steel comp 1021 or steel comp 1022 or steel comp 1025
Material Specification:
Astm a108 assn standard all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2, cl 3 federal specification single treatment response

NSN 5315-01-230-3705

Headless Shoulder Pin - Page 2 of 2



Thread Series Design	nator:
----------------------	--------

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0