## NSN 5315-01-231-2307

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-231-2307 **Shank Diameter:** Between 0.4970 inches and 0.4985 inches **Button Handle Diameter:** 1.300 inches **Detent Quantity: Lanyard Length:** 12.000 inches **Actuation Method:** Push button **Grip Length:** Between 6.100 inches and 6.120 inches **Actuation Type:** Push **Hardness Rating:** 58.0 rockwell c detent and 62.0 rockwell c detent Shear Strength: 32800 double pounds per square inch **Shoulder To Head End Distance:** 1.190 inches Pin Attachment Type: Cable lanyard w/terminations **Detent To Tapered End Distance:** Between 0.430 inches and 0.460 inches Material: Steel handle or aluminum alloy 2024 handle or aluminum alloy 2017 handle **Material Specification:** Qq-s-763 federal specification single material response detent **Surface Treatment:** Passivate detent **Surface Treatment Specification:** Qq-p-416, type 1 or 2, cl 2 federal specification single treatment response spindle **Style Designator: Button** Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A212a0

## NSN 5315-01-231-2307

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-t-6736 spec.