

View Online at <https://aerobasegroup.com/nsn/5315-01-232-7042>

**Head Diameter:**

0.510 inches

**Shank Diameter:**

Between 0.4345 inches and 0.4360 inches

**Ring Handle Diameter:**

1.090 inches

**Detent Quantity:**

2

**Lanyard Length:**

8.000 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 0.800 inches and 0.820 inches

**Actuation Type:**

Push

**Hardness Rating:**

58.0 rockwell c and 62.0 rockwell c detent

**Shear Strength:**

28000 double pounds per square inch

**Shoulder To Head End Distance:**

0.980 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

Between 0.350 inches and 0.380 inches

**Material:**

Steel comp 631 or steel comp 302 spring

**Material Specification:**

Qq-w-423 federal specification single material response ring

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response and qq-p-35 federal specification single treatment response

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5002 spec.