

View Online at <https://aerobasegroup.com/nsn/5315-01-234-9528>

First End Style:

Oval

Second End Style:

Slotted

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.475 inches and 0.525 inches

Shoulder Diameter:

Between 0.864 inches and 0.869 inches

Overall Length:

2.150 inches

First Step Diameter:

Between 0.746 inches and 0.748 inches

First Step Length:

Between 0.215 inches and 0.220 inches

Second Step Diameter:

Between 0.666 inches and 0.668 inches

Second Step Length:

Between 0.535 inches and 0.545 inches

Third Step Diameter:

Between 0.434 inches and 0.436 inches

Third Step Length:

Between 0.835 inches and 0.850 inches

Internal Drive Style:

Slot

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.106 inches and 0.110 inches

Distance From Centerline Of Hole To End Of Pin:

0.170 inches

Second End Slot Width:

0.130 inches

Second End Slot Depth:

0.120 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.437 inches

First End Location:

Shoulder end

First End Outer Radius:

Any acceptable

Second End Outer Radius:

Any acceptable

Special Features:

Hole located on threaded end

Material:

Steel comp 1018

Material Specification:

Astm a108 assn standard single material response

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, ty1 cl3 federal specification 1st treatment response or astm b633, ty1 sc1 assn standard 2nd treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0