## NSN 5315-01-236-9363

Headless Shoulder Pin - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5315-01-236-9363
First End Style:
Square
Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.405 inches
Shank Length:
0.517 inches
Shoulder Diameter:
0.438 inches
Shank Diameter:
Between 0.2490 inches and 0.2495 inches
Overall Length:
0.956 inches
Hole Arrangement Style:
One end drilled
First Hole Diameter:
Between 0.076 inches and 0.086 inches
Distance From Centerline Of Hole To End Of Pin:
0.140 inches
Second End Taper Length:
Between 0.250 inches and 0.252 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.250 inches
Second Shank Diameter:
Between 0.2490 inches and 0.2495 inches
First End Location:
Threaded end
Second End Tip Radius:
Between 0.060 inches and 0.090 inches
Second Shank Length:
0.314 inches
Material:
Steel comp 302 or steel comp 304 or steel comp 303
Material Specification:

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or astm a582 assn standard 3rd material response

## NSN 5315-01-236-9363

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A212a0