

View Online at <https://aerobasegroup.com/nsn/5315-01-237-4017>

**Head Diameter:**

Between 0.360 inches and 0.390 inches

**Shank Diameter:**

Between 0.245 inches and 0.248 inches

**Ring Handle Diameter:**

Between 1.000 inches and 1.187 inches

**Detent Quantity:**

2

**Grip Length:**

Between 1.300 inches and 1.320 inches

**Actuation Type:**

Push

**Shear Strength:**

4500 double pound

**Shoulder To Head End Distance:**

Between 0.380 inches and 0.560 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

Between 0.284 inches and 0.344 inches

**Material:**

Steel comp 302 spindle or steel comp 303 spindle or steel comp 304 spindle or steel comp 304l spindle or steel comp 305 spindle or steel comp 309 spindle or steel comp 310 spindle or steel comp 316 spindle or steel comp 316l spindle or steel comp 317 spindle or steel comp 321 spindle or steel comp 322 spindle or steel comp 324 spindle or steel comp 347 spindle or steel comp 303 plus x spindle or steel comp 303cu spindle or steel comp 303ma spindle or steel comp 303pb spindle or steel comp 303se spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0