NSN 5315-01-239-5998

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-239-5998

First End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.750 inches
Shank Length:
3.270 inches
Shoulder Diameter:
0.4375 inches
Shank Diameter:
Between 0.360 inches and 0.363 inches
Overall Length:
4.020 inches
First End Taper Length:
0.060 inches
Second End Relationship With First End:
Identical
Hardness Rating:
33.0 rockwell c and 38.0 rockwell c
Thread Size:
0.437 inches
First End Location:
Both ends
First End Taper Angle:
Between 40.0 degrees and 50.0 degrees
Material:
Steel comp e4340 or steel comp 4340
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-8844 military specification 2nd material response
Surface Treatment:
Cadmium or chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5315-01-239-5998

Headless Shoulder Pin - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5000 spec.