

View Online at <https://aerobasegroup.com/nsn/5315-01-240-8204>

**Shank Diameter:**

Between 0.3720 inches and 0.3735 inches

**Button Handle Diameter:**

Between 0.875 inches and 1.135 inches

**Detent Quantity:**

2

**Lanyard Length:**

Between 8.750 inches and 9.250 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 0.600 inches and 0.620 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c spindle and 40.0 rockwell c spindle

**Shear Strength:**

18400 double pound

**Shoulder To Head End Distance:**

1.040 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

0.365 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-s-6758 military specification single material response spindle

**Surface Treatment:**

Cadmium spindle or cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416 type 1 cl 3 federal specification 1st treatment response spindle or qq-p-416 type 2 cl 3 federal specification 2nd treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.