NSN 5315-01-241-0984

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-241-0984

Head Diameter:
Between 0.360 inches and 0.390 inches
Shank Diameter:
Between 0.245 inches and 0.248 inches
Ring Handle Diameter:
Between 1.000 inches and 1.187 inches
Detent Quantity:
2
Grip Length:
Between 2.100 inches and 2.120 inches
Actuation Type:
Push
Shear Strength:
4500 double pound
Shoulder To Head End Distance:
Between 0.380 inches and 0.560 inches
Pin Attachment Type:
Ring
Detent To Tapered End Distance:
Between 0.284 inches and 0.344 inches
Material:
Steel comp 302 spindle or steel comp 303 spindle or steel comp 304 spindle or steel comp 304l spindle or steel comp 305 spindle or stee
comp 309 spindle or steel comp 310 spindle or steel comp 316 spindle or steel comp 316l spindle or steel comp 317 spindle or steel comp
321 spindle or steel comp 322 spindle or steel comp 324 spindle or steel comp 347 spindle or steel comp 303 plus x spindle or steel comp
303cu spindle or steel comp 303ma spindle or steel comp 303pb spindle or steel comp 303se spindle
Surface Treatment:
Passivate spindle
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response spindle
Style Designator:
Ring handle
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A212a0